



FASTENERS

1/4" FASTENERS:

fasteners come with compatible 1/4" BSW STUD




FXNW
NUT AND WASHER
STUD
M.C.H Ø7




FXST
SPRING TOGGLE
M.C.H Ø17




FXTI
THREADED INSERT
PILOT Ø8




FXLB (1/4")
LAG BOLT
PILOT Ø4



FXFP (1/4")
FACE PLATE
1/4 B.S.W




FXMA
MASONRY ANCHOR
M.C.H Ø13




FXCA
CAVITY ANCHOR
M.C.H Ø12

FASTENERS M10:

fasteners supplied with M10 stud




FXBH
BALUSTRADE HEAD
M10
(316g)



FXCS
CAP SCREW
M.C.H Ø10.5
(VARIOUS
LENGTHS
AVAILABLE)




FXMA
MASONRY
ANCHOR LOXIN




FXFP (M10)
FACE PLATE
M10



FXTI
THREADED INSERT



FXTB
TOGGLE BOLT
M.C.H Ø23



FXLB (M10)
LAG BOLT
PILOT Ø8



FXAT
100mm ALL THREAD
can be used with chemset glue

1/4" WHITWORTH THREADED STUDS AVAILABLE:

- length 12mm
- length 16mm
- length 19mm
- length 22mm
- length 25mm
- length 27mm
- length 29mm
- length 32mm
- length 38mm
- length 51mm
- length 75mm
- length 100mm

M10 THREADED STUDS AVAILABLE:

- length 16mm
- length 20mm
- length 25mm
- length 30mm
- length 35mm
- length 40mm
- length 50mm
- custom length

*M.C.H =
MINIMUM CLEARANCE HOLE

*PILOT =
PILOT DRILL SIZE

PRODUCT COMPLIANCY:

As FIX Systems are not certified engineers, it is the buyer's responsibility to ensure that the application of all FIX products is suitable for its intended use and that it is compliant with relevant safety standards.

